

TEMU *GRPCI2 Model*

Mattias Holm

Version 1.0, 2019-12-12

Table of Contents

1. Introduction

2. Loading the Plugin

3. Configuration

4. Attributes

4.1. Properties

4.2. Interfaces

4.3. Ports

5. Registers

5.1. Register Bank default

6. Limitations

1

1

1

1

1

1

2

2

2

2

The use and/or disclosure,etc. of the contents of this document (or any part thereof) is subject to the restrictions referenced on the front page.

1. Introduction

The GRPCI2 model is available in the GrPci2 plugin.

2. Loading the Plugin

```
import GrPci2
```

3. Configuration

4. Attributes

4.1. Properties

Name	Type	Description
AHB2PCI	uint32_t	AHB to PCI mapping for PCI I/O
AHBM2PCI	[16 x uint32_t]	DMA channel active
BCIM	uint32_t	PCI master prefetch burst limit
CTRL	uint32_t	Control register
DMABASE	uint32_t	DMA descriptor base address
DMACHAN	uint32_t	DMA channel active
DMACTRL	uint32_t	GRPCI2 DMA control and status register
PCI2AHB	[6 x uint32_t]	DMA channel active
STATCAP	uint32_t	Status and Capability register
ioMem	iref / MemorySpaceIface	PCI i/o space object
irqCtrl	iref / IrqCtrlIface	Upward interrupt controller (i.e. on AMBA bus)
object.timeSource	object	Time source object (a cpu or machine object)
pciMem	iref / MemorySpaceIface	PCI memory space object

4.2. Interfaces

Name	Type	Description
ApbIface	ApbIface	APB P&P interface

Name	Type	Description
ConfigAccessIface	MemAccessIface	PCI config access interface.
IrqIface	IrqCtrlIface	PCI IRQ interface
MemAccessIface	MemAccessIface	Memory access interface (registers)
PCIBridgeIface	temu::PCIBridgeIface	PCI bridge interface.

4.3. Ports

Prop	Iface	Description
-	-	-

5. Registers



Register support is currently experimental!

5.1. Register Bank default

6. Limitations

- The device currently only supports one AHB master. Since most systems only have one (e.g. an AHB2AHB bridge), this limitation should not be a major issue.