

TEMU *GRPCI2 Model*

Mattias Holm

Version 1.0, 2019-12-12

Table of Contents

- 1. Introduction 1
- 2. Loading the Plugin 1
- 3. Configuration 1
- 4. Attributes 1
 - 4.1. Properties 1
 - 4.2. Interfaces 1
 - 4.3. Ports 2
- 5. Registers 2
 - 5.1. Register Bank default 2
- 6. Limitations 2

1. Introduction

The GRPCI2 model is available in the GrPci2 plugin.

2. Loading the Plugin

```
import GrPci2
```

3. Configuration

4. Attributes

4.1. Properties

Name	Type	Description
AHB2PCI	uint32_t	AHB to PCI mapping for PCI I/O
AHBM2PCI	[16 x uint32_t]	DMA channel active
BCIM	uint32_t	PCI master prefetch burst limit
CTRL	uint32_t	Control register
DMABASE	uint32_t	DMA descriptor base address
DMACHAN	uint32_t	DMA channel active
DMACTRL	uint32_t	GRPCI2 DMA control and status register
PCI2AHB	[6 x uint32_t]	DMA channel active
STATCAP	uint32_t	Status and Capability register
ioMem	iref / MemorySpaceIface	PCI i/o space object
irqCtrl	iref / IrqCtrlIface	Upward interrupt controller (i.e. on AMBA bus)
object.timeSource	object	Time source object (a cpu or machine object)
pciMem	iref / MemorySpaceIface	PCI memory space object

4.2. Interfaces

Name	Type	Description
ApbIface	ApbIface	APB P&P interface

Name	Type	Description
ConfigAccessIface	MemAccessIface	PCI config access interface.
IrqIface	IrqCtrlIface	PCI IRQ interface
MemAccessIface	MemAccessIface	Memory access interface (registers)
PCIBridgeIface	temu::PCIBridgeIface	PCI bridge interface.

4.3. Ports

Prop	Iface	Description
-	-	-

5. Registers



Register support is currently experimental!

5.1. Register Bank default

6. Limitations

- The device currently only supports one AHB master. Since most systems only have one (e.g. an AHB2AHB bridge), this limitation should not be a major issue.